



Overhead Stirrers	BDC6015	BDC3030	BDC1850	BDC2010	BDC2002	BDC250	Stands/Clamp	A110	A210	A120
Speed Range	40-6000 rpm	20-3000 rpm	12-1800 rpm	40-2010 rpm	40-2000 rpm	50-2500 rpm	Best choice for	BDC6015	BDC2010	All
Max Torque	170 Ncm	339 Ncm	565 Ncm	100 Ncm	70 Ncm	10 Ncm		BDC3030	BDC2002	
Max Viscosity	20,000 cps	50,000 cps	90,000 cps	20,000 cps	15,000 cps	Water like		BDC1850		
Horsepower	1/5 hp	1/5 hp	1/5 hp	1/10 hp	1/15 hp	1/100 hp				
Volume	25 liters	60 liters	80 liters	25 liters	25 liters	2 liters				

labsales@caframo.com

www.caframo.com

Phone: 1-800-567-3556

## Blades & Impellers



	A130	A131	A231	A140	A141	A150	A250	A166	A180	A183	A185	U022	U044SW
Impeller L x H (mm)	50 x 12	50 x 12	31 x 12	60 x 15	90 x 10	70 x 70	38 x 38	64 Ø	38 Ø	80 Ø	38 Ø	50 x 50	148 x 152
Shaft Ø (mm)	8	8	8	8	8	8	8	8	8	8	8	8	9.5
Shaft Length (mm)	400	400	400	400	400	400	400	400	400	400	400	400	910



	U044	U055	U510	A511	A521	A531	A533	A541	A551	A553	A165	A163	A164
Impeller L x H (mm)	101 x 101	127 x 127	254 x 127	25 Ø	38 Ø	51 Ø	51 Ø	76 Ø	51 Ø	51 Ø	64 Ø	41 x 12.7	48 Ø
Shaft Ø/Bore Ø	9.5	9.5	9.5	8	8	8	9.5	8	8	9.5	8	8	8
Shaft Length	910	910	910	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a

**Shafts** available in 8 or 9.5 mm Ø and 300, 400, 457, 508, 610, and 762 mm lengths